

IP22 Class II (VI)

Product Features


- Meets medical & I.T.E. safety
- 2 MOPP input to output isolation
- Touch current $\leq 10\mu\text{A}$
- Energy efficiency level VI
- $\leq 0.075\text{W}$ standby power
- 5V to 24V outputs, up to 12W
- Up to 5,000m operating altitude
- Interchangeable AC plugs
- UES12LCP2-SPC (Lithium-ion battery charger)



Models & Ratings

Model Number	Voltage ^(*) (V)	Current (A)	Rated Power	Ripple & Noise (max) ^(*) (²)	Voltage Tolerance	Line & Load Regulation	Efficiency (Average)	Start Up Delay
UES12LCP2-XXXXYYSPA UES12LCP2-XXXXYYSPC	4.0-5.0	0.01-2.00	10.00W	150mVpk-pk	$\pm 7\%$	Line: $\pm 1\%$ Load: $\pm 5\%$	79.01%	$\leq 3\text{s}$
	5.1-5.9	0.01-2.00	11.80W	150mVpk-pk	$\pm 7\%$		80.19%	$\leq 3\text{s}$
	6.1-7.0	0.01-1.71	12.00W	150mVpk-pk	$\pm 7\%$		83.30%	$\leq 3\text{s}$
	7.1-8.0	0.01-1.50	12.00W	150mVpk-pk	$\pm 7\%$		83.30%	$\leq 3\text{s}$
	8.1-9.0	0.01-1.33	12.00W	150mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	9.1-10.0	0.01-1.20	12.00W	150mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	10.1-11.0	0.01-1.09	12.00W	150mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	11.1-12.0	0.01-1.00	12.00W	150mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	12.1-13.0	0.01-0.94	12.00W	200mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	13.1-14.0	0.01-0.86	12.00W	200mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	14.1-15.0	0.01-0.80	12.00W	200mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	15.1-16.0	0.01-0.75	12.00W	200mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	16.1-17.0	0.01-0.71	12.00W	200mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	17.1-18.0	0.01-0.67	12.00W	200mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	18.1-19.0	0.01-0.63	12.00W	200mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	19.1-20.0	0.01-0.60	12.00W	200mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	20.1-21.0	0.01-0.57	12.00W	200mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	21.1-22.0	0.01-0.55	12.00W	200mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	22.1-23.0	0.01-0.52	12.00W	200mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$
	23.1-24.0	0.01-0.50	12.00W	200mVpk-pk	$\pm 5\%$		83.30%	$\leq 3\text{s}$

Mechanical Details



Interchangeable AC Plug Options^(*)

US/Japan Europe UK Australia China

DC cable and connector can be customized. Unit: mm

Notes

(*1, 3) Other options are available, please contact our sales representative for details.
 (*2) Measured at output connector with 20MHz bandwidth and 0.1uF ceramic in parallel with 10uF electrolytic capacitors.

Input

Input Voltage Range	80-264VAC
Frequency Range	47-63Hz
Input Current	0.5A at 90VAC
Inrush Current	50A max at 240VAC cold start
Touch Leakage Current ^(max)	≤10μA at 264VAC

Environmental

Operating Temperature	0°C to 45°C
Storage Temperature	-20°C to 60°C
Operating Humidity	10% to 90% RH, non-condensing
Storage Humidity	5% to 90% RH
Operating Altitude	5,000m

General

Dimensions	76.5(L) 32.5(W) 58.0(H)mm
Weight	130g
MTBF	>100,000hrs MIL-HDBK-217 at 25°C

Protection

Overload	120-200% rated output power, auto recovery
Over Voltage	120-150% rated output voltage input to reset
Short Circuit	Trip and restart (hiccup mode)

Safety Approvals

Safety Agency / Mark	Medical(Meet)	ITE(Meet)
CB	IEC60601-1/IEC60601-1-11	IEC62368-1
UL	ANSI/AAMI ES60601-1/60601-1-11 CAN/CSA C22.2 NO. 60601-1	UL62368-1
TüV Rheinland/Mark	EN60601-1/EN60601-1-11	-
TüV Rheinland/GS	-	EN62368-1
RCM	-	AS/NZS 62368
CE	-	EN62368
CCC	-	GB4943.1
PSE	-	J62368
KC	-	K60950-1
FCC	-	FCC PART 15

EMC

Emissions	Medical	ITE
Conducted	IEC/EN 60601-1-2, CISPR 11	EN55032, CISPR 32
Radiated	IEC/EN 60601-1-2, CISPR 11	EN55032, CISPR 32
Harmonic Currents	EN61000-3-2, Class A	EN61000-3-2, Class A
Voltage Flicker	EN61000-3-3	EN61000-3-3
Immunity	IEC/EN 60601-1-2	EN55024, CISPR 24
ESD	EN61000-4-2	±15kV air, ±8kV contact
Radiated Immunity	EN61000-4-3	10V/m, 3V/m 80MHz - 2.7GHz
EFT/Burst	EN61000-4-4	±2kV on AC port, ±1kV on signal ports
Surge	EN61000-4-5	±1KV line to line (different mode)
Conducted Immunity	EN61000-4-6	3Vrms, 6Vrms (0.15MHz-80MHz)
Magnetic Field	EN61000-4-8	30 A/m
Dips & Interruptions	EN61000-4-11	0%, 70%, 0% of UT

Others

Dielectric Withstand Voltage	5,656VDC input to output
Insulation Resistance	10M Ohms, 500VDC input to output