

Power Strip UEP65Y322V

Features

- ◆ AC input voltage range 90-264VAC
- ◆ 3 standard AC sockets
- ◆ 2 standard Type-C output ports; 2 USB-A output port;
It can fast charging more devices at the same time
- ◆ Protections against: short circuit/over current/over voltage/over temperature
- ◆ Safety protection. Sub control button, which can control on/off of each AC socket;
- ◆ Type-C Support PD3.0, PPS, QC3.0, QC2.0 Fast charging protocol
- ◆ USB-A Support QC3.0, QC2.0 Fast charging protocol
- ◆ When charging multiple devices simultaneously, intelligent power distribution enables each device to get optimal charging;

NEW



Power module data (UEP65Y322V)

Input Voltage Range	90-264VAC	Operating Temperature	0~25℃	Storage Temperature	-40~80℃
Input Current	1.7A	Operating Humidity	5% to 95% non condensing		
Output Voltage Tolerance	±5%	Height	≤ 5000m		
		MTBF	100,000 hours at full load at 25℃ ambient, calculated per MIL-HDBK-217		
Standby Power	0.3W Max				
Safety Standard	Meet CB(IEC60884-1), CE(EN62368-1)				
Weight	About 500g	Dimensions	279.0mm (L) ; 70.0mm (W) ; 27.5mm (H)		
Applications	Notebook, Mobile phone, Game console, PDA and other charging devices				

Output data(UEP65Y322V)

Output Port Combination

Type-C1/C2	5V/9V/12V/15V, 3A, 20V/3.25A, 65W Max
SB-A1	5V/1A, 5W Max
USB-A2	5V/3A, 9V/3A, 12V/3A, 20V/3A, 60W Max
Type-C1+C2	45W+20W; 65W Max
USB-A1+A2	5W+18W; 23W Max
Type-C1+A2	45W+18W; 63W Max
Type-C2+A1	60W+5W; 65W Max
Type-C1+A1	60W+5W; 65W Max
Type-C2+A2	5V/3A; 15W Max
Type-C2+C1+A1	20W+40W+5W; 65W Max
Type-C1+C2+A2	45W+5V3A; 60W Max
Type-A2+C1+A1	18W+40W+5W; 63W Max
Type-A1+C2+A2	5W+5V3A; 20W Max
Type-C1+A1+C2+A2	40W+5W+5V3A; 60W Max

AC Jack data(UEP65Y322V)

Rated Voltage : 250V~

Maximum current : 16A Max

Maximum power : 4000W Max

Standard

EMC standard	EN55032/CISPR32; EN55035/CISPR35
Conduction & Radiation	EN55032/CISPR32 Class B
Harmonic Currents	IEC/EN 61000-3-2 Class A
Voltage Flicker	IEC/EN 61000-3-3
ESD	IEC/EN 61000-4-2 ±8KV Air, ±4KV Contact
Radiated Immunity	IEC/EN 61000-4-3 3V/m
EFT/Burst	IEC/EN 61000-4-4 ±1KV
Surge	IEC/EN 61000-4-4 ±1KV DM, ±2KV CM
Conducted Immunity	IEC/EN 61000-4-6 3Vrms
Dips & Interruptions	IEC/EN 61000-4-11 0%, 70%, 0% of UT