

Charger UES1260-SPA3

产品特性

- ◆ AC input voltage range 90-264VAC
- ◆ Protections against: short circuit/over current/over voltage
- ◆ DC output voltage 60-84VDC
- ◆ The screen displays charging information



Input Voltage Range	90-264VAC	Operating Temperature	-20~50°C
Input Current	10A	Storage Temperature	-30~80°C
Full load efficiency	90% MIN	Operating Humidity	5% to 90% non condensing
Output Voltage	60-84V	MTBF	200,000 hours at full load at 25°C ambient, calculated per Telcordia_SR-332
Standby Power	3.0W Max		
Safety Standard	Meet CE(EN60335)		
Weight	About 1930g	Dimensions	250.0mm (L); 158.0mm (W); 78.0mm (H)
Applications	Lead-acid batteries, Lithium batteries		

Output data (UES1260-SPA3)

Model	Voltage (V)	Current (A)	Ripple (mV)	Av. Eff. (%) Min	Input Voltage (VAC)
UES1260-8401500SPA3	60.0-84.0	15	500	92.00	180.0-240.0
UES1260-8401500SPA3	60.0-84.0	10	500	90.00	100.0-170.0

Standard

Conduction & Radiation	EN55014 Class A
Harmonic Currents	IEC/EN 61000-3-2 Class A
Voltage Flicker	IEC/EN 61000-3-3
ESD	IEC/EN 61000-4-2 ±6KV Air, ±8KV Contact Class B
Radiated Immunity	IEC/EN 61000-4-3 3V/m Class B
EFT/Burst	IEC/EN 61000-4-4 ±1KV Class B
Surge	IEC/EN 61000-4-5 ±1KV P-N, ±2KV P/N-PE
Conducted Immunity	IEC/EN 61000-4-6 3Vrms Class B
Dips & Interruptions	IEC/EN 61000-4-11 100% 100% 30% Dip, 100% Int